

Suspended decorative luminaire for LED light sources.

#### TECHNICAL DATA

**Mounting:** suspended, on wire suspension (included)  
**Body:** powder painted steel sheet and top quality plastic  
**Colour:** ecru

#### ELECTRICAL DATA

**Diffuser:** opal plexiglass (PLX)  
**Power:** 220-240V 50/60Hz  
**Includes light source:** yes  
**Type of equipment:** ED

#### OPTICAL DATA

**Way of lighting:** direct

#### ADDITIONAL INFO

**Available on request:** DALI


#### GENERAL DATA

**Warranty:** 3 years + 2 years after project registration  
**Application:** offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
210020.5L01.112	120°	3x10	40	3000	2100	52	4000	≥81
210020.5L02.112	120°	3x10	40	3000	2100	52	3000	≥81

Code	Dimensions [mm] L W H D	Pallet quantity	Quantity in package	Net weight [kg]
210020.5L01.112	1000 81 165 885	24	1	4.5
210020.5L02.112	1000 81 165 885	24	1	4.5



#### OTHER PICTURES



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.


Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info available on our website [www.flashdq.com](http://www.flashdq.com)

Date of issue: 26-2-2016

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires

## LIGHT BEAM CURVES



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info available on our website [www.flashdq.com](http://www.flashdq.com)

Date of issue: 26-2-2016

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires