



















Modern downlight luminaire for LED light sources for plaster board cellings.

TECHNICAL DATA

Mounting: in the ceiling, with mounting brackets (included)

Body: powder painted steel sheet and anodized aluminum

Colour: white, black

ELECTRICAL DATA Power: 220-240V 50/60Hz

Includes light source: yes Type of equipment: ED

OPTICAL DATA **ADDITIONAL INFO**

GENERAL DATA

Way of lighting: direct


Available on request: metal halide lamps (on request), DALI Other remarks: for metal halide version - please order MH light sources

Warranty: 3 years + 2 years after project registration


Application: hotels, offices, delicatessen, galleries, boutiques, shopping centers



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
22002X.5L201.3X2	24°	2x17,5	42	2x1560	3120	74	4000	92
22002X.5L202.3X2	24°	2x17,5	42	2x1430	2860	68	3000	92
22002X.5L203.3X2	40°	2x17,5	42	2x1560	3120	74	4000	92
22002X.5L204.3X2	40°	2x17,5	42	2x1430	2860	68	3000	92



Code	Dimensions [mm] L W H	Pallet quantity	Quantity in package	Net weight [kg]
22002X.5L201.3X2	348 196 144	70	1	3.2
22002X.5L202.3X2	348 196 144	70	1	3.2
22002X.5L203.3X2	348 196 144	70	1	3.2
22002X.5L204.3X2	348 196 144	70	1	3.2





Designed by LUG Design Team





LIGHT BEAM CURVES

