

Modern surface mounted luminaire for LED light sources.

TECHNICAL DATA

Mounting: surface mounted
Body: anodized aluminum profile
Colour: black
Diffuser: opal plexiglass (PLX), microprismatic diffuser (MPRM)

ELECTRICAL DATA

Power: 220-240V 50/60Hz
Includes light source: yes
Type of equipment: ED

OPTICAL DATA

Way of lighting: direct

ADDITIONAL INFO

Available on request: DIM 1..10V, DALI

GENERAL DATA

Warranty: 3 years + 2 years after project registration
Application: offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques, airports



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
200073.5L01.21X	120°	39	45	5400	4050	90	3000	≥81
200073.5L02.21X	120°	39	45	5550	4180	93	4000	≥81
200073.5L03.22X	120°	71	82	9850	7400	90	3000	≥81
200073.5L04.22X	120°	71	82	10200	7650	93	4000	≥81
200073.5L05.23X	120°	174	200	24200	18150	91	3000	≥81
200073.5L06.23X	120°	174	200	25000	18810	94	4000	≥81


200073.5L01.21



Type of raster / diffuser

- 1 satin
- 2 microprismatic diffuser

Code	Dimensions [mm] W H	Pallet quantity	Quantity in package	Net weight [kg]
200073.5L01.21X	450 105	6	1	6.0
200073.5L02.21X	450 105	6	1	6.0
200073.5L03.22X	650 105	6	1	10.3
200073.5L04.22X	650 105	6	1	10.3
200073.5L05.23X	950 105	3	1	20.3
200073.5L06.23X	950 105	3	1	20.3



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info available on our website www.flashdq.com

Date of issue: 26-2-2016

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires