

Modern surface mounted luminaire for LED light sources.

#### TECHNICAL DATA

**Mounting:** surface mounted

**Body:** anodized aluminum profile

**Colour:** black

**Diffuser:** microprismatic diffuser (MPRM), opal plexiglass (PLX)

#### ELECTRICAL DATA

**Power:** 220-240V 50/60Hz

**Includes light source:** yes

**Type of equipment:** ED

#### OPTICAL DATA

**Way of lighting:** direct

#### ADDITIONAL INFO

**Available on request:** DIM 1..10V, DALI

**Operating temperature range:** 0° C... +25° C

**Lifetime (L70B50):** 50 000 h

#### GENERAL DATA

**Warranty:** 3 years + 2 years after project registration

**Application:** offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques, airports



| Code            | Beam angle | Power LED [W] | Luminaire power [W] | Lumen LED [lm] | Lumen luminaire [lm] | Efficacy [lm/W] | Colour temperature [K] | CRI/Ra |
|-----------------|------------|---------------|---------------------|----------------|----------------------|-----------------|------------------------|--------|
| 200063.5L01.21X | 120        | 39            | 46                  | 5400           | 4250                 | 92              | 3000                   | ≥81    |
| 200063.5L02.21X | 120        | 39            | 46                  | 5550           | 4400                 | 96              | 4000                   | ≥81    |
| 200063.5L03.21X | 120        | 174           | 204                 | 24200          | 19120                | 94              | 3000                   | ≥81    |
| 200063.5L04.21X | 120        | 174           | 204                 | 25000          | 19800                | 97              | 4000                   | ≥81    |


#### 200063.5L01.11



Type of raster / diffuser

- 1 satin
- 2 microprismatic diffuser

| Code            | Dimensions [mm]<br>W H | Quantity in package | Net weight [kg] |
|-----------------|------------------------|---------------------|-----------------|
| 200063.5L01.21X | 450 100                | 1                   | 5.8             |
| 200063.5L02.21X | 450 100                | 1                   | 5.8             |
| 200063.5L03.21X | 950 100                | 1                   | 20.0            |
| 200063.5L04.21X | 950 100                | 1                   | 20.0            |



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info available on our website [www.flashdq.com](http://www.flashdq.com)

Date of issue: 26-2-2016

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires