

Suspended decorative luminaire for LED light sources.

<b>TECHNICAL DATA</b>	<b>Mounting:</b> suspended, on wire suspension (included) <b>Body:</b> anodized aluminum profile <b>Colour:</b> black <b>Diffuser:</b> opal plexiglass (PLX), microprismatic diffuser (MPRM)
<b>ELECTRICAL DATA</b>	<b>Power:</b> 220-240V 50/60Hz <b>Includes light source:</b> yes <b>Type of equipment:</b> ED
<b>OPTICAL DATA</b>	<b>Way of lighting:</b> direct
<b>ADDITIONAL INFO</b>	<b>Available on request:</b> DIM 1..10V, DALI <b>Operating temperature range:</b> 0°C ... +25°C <b>Lifetime (L70B50):</b> 50 000 h
<b>GENERAL DATA</b>	<b>Warranty:</b> 3 years + 2 years after project registration <b>Application:</b> offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques, airports




Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
200063.5L01.11X	120	39	46	5400	4050	88	3000	≥80
200063.5L02.11X	120	39	46	5550	4180	91	4000	≥80
200063.5L03.11X	120	174	204	24200	18150	89	3000	≥80
200063.5L04.11X	120	174	204	25000	18810	92	4000	≥80

200063.5L01.11



- Type of raster / diffuser
- 1 satin
  - 2 microprismatic diffuser

Code	Dimensions [mm] W H	Pallet quantity	Quantity in package	Net weight [kg]
200063.5L01.11X	450 100	6	1	5.8
200063.5L02.11X	450 100	6	1	5.8
200063.5L03.11X	950 100	3	1	20.0
200063.5L04.11X	950 100	3	1	20.0



EN

**TLON z/w**

Group in catalogue: FLASH&DQ

FLASH&DQ

OTHER PICTURES

---



TLON Ø450

Designed by LUG Design Team

Date of issue: 17-3-2016

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires